

1. SCOPE

This specification outlines the pertinent electrical requirements of the RF output modulator which converts the FM video and FM audio signal into the RF signal for television standard transmission system.

2. GENERAL SPECIFICATIONS

2-1. Output frequency 2400~2483 MHz (I²C PLL controller from outside)

2-2.

2-3. Supply voltage 12V+/-0.2V

2-4. Consumption current 140+/-20 mA

2-5. Operation and storage temperature 0-50°C
Conditions for guarantee humidity 85% or less

3. TEST CONDITIONS

3-1. Testing ambient conditions defined as temperature of 25+/-2°C and humidity of 65+/-5% RH

Note: that temperatures of 5~30°C and humidity of 45-85%rh may be regarded as standard.

3-2. Unit setting conditions

1) Picture --10 step wave signal 1.0 Vp-p(82 ohm load)

2) Audio -- 1.0Vp-p of sine wave 1KHz



4. ELECTRICAL PERFORMANCE						
4-1. Video system characteristics						
		Specification				
	Parameter	min	typ	max	unit	Remark
4-1-1	Input impedance			1.3	K	measure at 0.5 ~ 5 MHz
4-1-2	Input signal level			1	Vp-p	load of 92 ohm connected negative synchronous
4-1-3	Modulation fp 2480 MHz (sine wave 300KHz 1Vp-p)	2	3	4	MHz	Superimposed sinuous wave (2.58 MHz) is 20% of the step input level. Measure with under the APL of 10~90% differential gain of demodulator unit is to be compensated..
4-1-4	Differential gain	8		8	%	
4-1-5	Differential phase	-8		8	deg	-ditto-
4-1-6	S/N	45			dB	Measure with respect to standard demodulator output.
4-1-7	Out level taper		4	6	dB	Fp 2400~2483mhz.
4-2. Audio system characteristics						
4-2-1	Input impedance		1.4		Kohm	Measure at 0.1-10khz
4-2-2	Modulation	35	40	45	khz	
4-2-3	Distortion factor			3	%	Audio input signal 1.0Vp-p 1khz modulation 50% (sine wave). Video input signal all black (sync.only) use standard demodulator of inter-carrier system. De-emphasis(50 usec) is on.
4-2-4	S/n	40			dB	



4-3. Output system characteristics							
Parameter		Specification.				Remark	
		min	typ	max	unit		
4-3-1	Video carrier frequency	-50	fp	+50	KHz	Test at 25°C temperature and 65% RH of humidity Fp 2400~2483 Mhz Fs1 6.5 mhZ Fs2 6.5 mhz *output channel	
4-3-2	Video output level	13	14	16	dBm		
4-3-3	Audio output level difference(P/S ratio)	22	27	32	dB		
4-3-4	Audio carrier frequency	-8	fs	+8	KHz	Input signal none the measurement is taken after 30 sec. from the power-on.	
4-3-5	Audio modulator fs1 fs2	35	50	65	KHz	Measurement difference video of carrier frequency output level for 2400~2483 Mhz except to fp. fp+/-fs against video carrier output level.	
		35	50	65			
4-3-6	Out-band spurious	50	55		dB		
4-3-7	In-band spurious within bandwidth	60			dB		
4-3-8	Output impedance		75		ohm		Unbalanced.



5-1. PLL section characteristics												
No	Item	Specification									notes	
5-2.	(1) SDA SCL input voltage	Under standard test condition									V	
		Condition	Min	Typ	Max							
	High voltage	3		5								
	Low voltage	0		1.5								
	(2) Address	C2 (on write date format)										
	(3) SDA SCL input impedance	SDA/SCL are in the high impedance and there should be no reliability problem with 5V continually on the SDA/SCL, if power supply is switched off.										
	(4) Data format	MSB					LSB					
	Address	1	1	0	0	0	MA1	MA0	0	A	Byte1	
	Programmable Divider	0	2	2	2	2	2	2	2	A	Byte2	
	Programmable Divider	7	6	5	4	3	2	1	0	A	Byte3	
	Charge pump and test bits	1	(0) CP	T1	T0	1	1	1	(0) os	A	Byte4	
	I/O port control bits	P7	P6	P5	P4	P3	P2	P1	P0	A	Byte5	
	Table 1 write data format (MSB is transmitted first)											
	Address	1	1	0	0	0	Ma1	Ma2	1	A	Byte1	
	Status byte	POR	FL	I2	I1	I0	A2	A1	A0	A	Byte2	
	<p>Table 2 read date format</p> <p>A: acknowledge bit.</p> <p>Ma1, Ma0: voltage address bits.</p> <p>CP: charge pump current select.</p> <p>T1: test mode selection, T0: charge pump disable</p> <p>OS: varactor drive output disable switch.</p> <p>P7, P6, P5, P4, P3, P2, P1, P0: control output states</p> <p>POR: power on reset indicator</p> <p>PL: phase lock detect flag</p> <p>I2, I1, I0: digital information from ports P7, P5, and P4.</p> <p>A2, A1, A0: 5 level ADC data from P6</p>											

